


SMD - Induktivitäten 1206

ohne Umhüllung

Miniaturausführung 3.2 x 1.6 x 1.8 mm



Induktivität	Güte	R Ω	I max. mA	f res MHz	Best.Nr.	St.	ab 10	ab 100	ab 500
0.22 μH	20	0.4	240	250	7656/221	-.950	-.563	-.375	-.300
0.47 μH	30	0.6	210	210	7656/471	-.950	-.563	-.375	-.300
0.68 μH	30	0.7	190	160	7656/681	-.950	-.563	-.375	-.300
1.0 μH	35	0.5	175	100	7656/102	-.950	-.563	-.375	-.300
3.3 μH	35	1.5	280	40	7656/332	-.950	-.563	-.375	-.300
4.7 μH	35	1.7	120	31	7656/472	-.950	-.563	-.375	-.300
10 μH	35	2.5	100	20	7656/103	-.950	-.563	-.375	-.300
100 μH	40	12	45	7	7656/104	-.950	-.563	-.375	-.300

Nettopreise in € per St. ab Lager Nürnberg, zuzügl. der gesetzl. Mehrwertsteuer

MIRA-ELECTRONIC

Dipl. Ing. (FH) Gerhard Sauerbeck

www.MIRA-ELECTRONIC.de

info@MIRA-ELECTRONIC.de

Tel. 0911 / 55 59 19

Fax. 0911 / 58 13 41