

Baugröße 00603 Hochvolt (max. Spannung $\geq 100V$)

Wert	Bauform/Keramik/Spg./Toleranz	Best.Nr.	ab 10	ab 100	ab 500	ab 1000	ab 4000
10pF	0603 NP0 100V $\pm 5\%$	8220/100-1	-.150	-.0289	-.0194	-.0163	-.0097
15pF	0603 NP0 100V $\pm 5\%$	8220/150-1	-.150	-.0233	-.0148	-.0123	-.0072
22pF	0603 NP0 100V $\pm 5\%$	8220/220-1	-.150	-.0302	-.0205	-.0173	-.0103
33pF	0603 NP0 100V $\pm 5\%$	8220/330-1	-.150	-.0302	-.0205	-.0173	-.0103
47pF	0603 NP0 100V $\pm 5\%$	8220/470-1	-.150	-.0267	-.0175	-.0147	-.0087
68pF	0603 NP0 100V $\pm 5\%$	8220/680-1	-.150	-.0293	-.0198	-.0166	-.0099
100pF	0603 NP0 100V $\pm 5\%$	8220/101-1	-.150	-.0293	-.0198	-.0166	-.0099
150pF	0603 NP0 100V $\pm 5\%$	8220/151-1	-.220	-.0412	-.0297	-.0253	-.0153
220pF	0603 NP0 100V $\pm 5\%$	8220/221-1	-.220	-.0399	-.0286	-.0243	-.0147
330pF	0603 NP0 100V $\pm 5\%$	8220/331-1	-.220	-.0280	-.0187	-.0157	-.0093
470pF	0603 NP0 100V $\pm 5\%$	8220/471-1	-.220	-.0280	-.0187	-.0157	-.0093
680pF	0603 NP0 100V $\pm 5\%$	8220/681-1	-.220	-.0421	-.0304	-.0259	-.0157
1.0nF	0603 NP0 100V $\pm 5\%$	8220/102-1	-.220	-.0326	-.0225	-.0190	-.0114
1.0nF	0603 X7R 100V $\pm 10\%$	8221/102-1	-.150	-.0236	-.0150	-.0125	-.0073
1.5nF	0603 X7R 100V $\pm 10\%$	8221/152-1	-.210	-.0258	-.0168	-.0141	-.0083
2.2nF	0603 X7R 100V $\pm 10\%$	8221/222-1	-.210	-.0258	-.0168	-.0141	-.0083
3.3nF	0603 X7R 100V $\pm 10\%$	8221/332-1	-.210	-.0258	-.0168	-.0141	-.0083
4.7nF	0603 X7R 100V $\pm 10\%$	8221/472-1	-.210	-.0280	-.0187	-.0157	-.0093
6.8nF	0603 X7R 100V $\pm 10\%$	8221/682-1	-.210	-.0280	-.0187	-.0157	-.0093
10nF	0603 X7R 100V $\pm 10\%$	8221/103-1	-.210	-.0258	-.0168	-.0141	-.0083
100nF	0603 X7R 100V $\pm 10\%$	8221/104-1	-.300	-.0448	-.0326	-.0278	-.0169

weitere Werte auf Anfrage lieferbar

Baugröße 0805 Hochvolt max. Spannung 100V / 250V

10pF	0805 NP0 100V $\pm 5\%$	8230/100-1	-.150	-.0368	-.0260	-.0219	-.0133
15pF	0805 NP0 100V $\pm 5\%$	8230/150-1	-.150	-.0368	-.0260	-.0219	-.0133
22pF	0805 NP0 100V $\pm 5\%$	8230/220-1	-.150	-.0368	-.0260	-.0219	-.0133
33pF	0805 NP0 100V $\pm 5\%$	8230/330-1	-.150	-.0301	-.0204	-.0170	-.0103
47pF	0805 NP0 100V $\pm 5\%$	8230/470-1	-.150	-.0316	-.0217	-.0181	-.0109
68pF	0805 NP0 100V $\pm 5\%$	8230/680-1	-.180	-.0368	-.0260	-.0219	-.0133
100pF	0805 NP0 100V $\pm 5\%$	8230/101-1	-.150	-.0370	-.0262	-.0220	-.0134
150pF	0805 NP0 100V $\pm 5\%$	8231/151-1	-.180	-.0525	-.0391	-.0333	-.0204
220pF	0805 NP0 100V $\pm 5\%$	8230/221-1	-.180	-.0525	-.0391	-.0333	-.0204
330pF	0805 NP0 100V $\pm 5\%$	8230/331-1	-.160	-.0373	-.0264	-.0222	-.0135
470pF	0805 NP0 100V $\pm 5\%$	8230/471-1	-.160	-.0366	-.0258	-.0217	-.0132
680pF	0805 NP0 100V $\pm 5\%$	8230/681-1	-.180	-.0403	-.0289	-.0244	-.0149
1.0nF	0805 NP0 100V $\pm 5\%$	8230/102-1	-.180	-.0468	-.0343	-.0291	-.0178
1.0nF	0805 X7R 100V $\pm 10\%$	8231/102-1	-.150	-.0293	-.0198	-.0164	-.0099
1.0nF	0805 X7R 250V $\pm 10\%$	8231/102-2	-.180	-.0368	-.0260	-.0219	-.0133
1.5nF	0805 X7R 100V $\pm 10\%$	8231/152-1	-.160	-.0390	-.0278	-.0235	-.0143
1.5nF	0805 X7R 250V $\pm 10\%$	8231/152-2	-.220	-.0542	-.0405	-.0345	-.0212
2.2nF	0805 X7R 100V $\pm 10\%$	8231/222-1	-.150	-.0290	-.0195	-.0162	-.0098
2.2nF	0805 X7R 250V $\pm 10\%$	8231/222-2	-.220	-.0372	-.0264	-.0222	-.0135
3.3nF	0805 X7R 100V $\pm 10\%$	8231/332-1	-.170	-.0390	-.0278	-.0235	-.0143
4.7nF	0805 X7R 100V $\pm 10\%$	8231/472-1	-.150	-.0289	-.0194	-.0162	-.0097
4.7nF	0805 X7R 250V $\pm 10\%$	8231/472-2	-.220	-.0542	-.0405	-.0345	-.0212
6.8nF	0805 X7R 100V $\pm 10\%$	8231/682-1	-.170	-.0390	-.0278	-.0235	-.0143
10nF	0805 X7R 100V $\pm 10\%$	8231/103-1	-.150	-.0285	-.0191	-.0159	-.0095
10nF	0805 X7R 250V $\pm 10\%$	8231/103-2	-.170	-.0652	-.0497	-.0424	-.0261

Nettopreise in € per St. ab Lager Nürnberg, zuzügl. der gesetzl. Mehrwertsteuer

MIRA-ELECTRONIC

Dipl. Ing. (FH) Gerhard Sauerbeck

www.MIRA-ELECTRONIC.de

info@MIRA-ELECTRONIC.de

Tel. 0911 / 55 59 19

Fax. 0911 / 58 13 41

Wert	Bauform/Keramik/Spg./Toleranz	Best.Nr.	ab 10	ab 100	ab 500	ab 1000	ab 4000
22nF	0805 X7R 100V ±10%	8231/223-1	-.150	-.0734	-.0565	-.0484	-.0299
47nF	0805 X7R 100V ±10%	8231/473-1	-.280	-.0574	-.0432	-.0368	-.0226
100nF	0805 X7R 100V ±10%	8231/104-1	-.180	-.0411	-.0296	-.0250	-.0152

weitere Werte auf Anfrage lieferbar

Baugröße 1206 Hochvolt max. Spannung 100 / 250 / 500 / 630 / 1000 / 2000 V

Wert	Bauform/Keramik/Spg./Toleranz	Best.Nr.	ab 10	ab 100	ab 500	ab 1000	ab 4000
10pF	1206 NP0 100V ±5%	8240/100-1	-.290	-.1106	-.0871	-.0751	-.0467
15pF	1206 NP0 100V ±5%	8240/150-1	-.290	-.1106	-.0871	-.0751	-.0467
22pF	1206 NP0 100V ±5%	8240/220-1	-.290	-.1106	-.0871	-.0751	-.0467
33pF	1206 NP0 100V ±5%	8240/330-1	-.290	-.1106	-.0871	-.0751	-.0467
47pF	1206 NP0 100V ±5%	8240/470-1	-.290	-.1106	-.0871	-.0751	-.0467
68pF	1206 NP0 100V ±5%	8240/680-1	-.290	-.1106	-.0871	-.0751	-.0467
100pF	1206 NP0 100V ±5%	8240/101-1	-.250	-.0757	-.0580	-.0499	-.0309
100pF	1206 NP0 500V ±5%	8240/101-5	-.290	-.0971	-.0759	-.0654	-.0406
150pF	1206 NP0 100V ±5%	8240/151-1	-.270	-.1108	-.0873	-.0753	-.0468
220pF	1206 NP0 100V ±5%	8240/221-1	-.250	-.0870	-.0675	-.0581	-.0360
330pF	1206 NP0 100V ±5%	8240/331-1	-.250	-.0859	-.0666	-.0573	-.0355
470pF	1206 NP0 100V ±5%	8240/471-1	-.270	-.0980	-.0766	-.0660	-.0410
470pF	1206 X7R 1 kV ±10%	8241/471-9	-.300	-.1206	-.0954	-.0824	-.0512
680pF	1206 NP0 100V ±5%	8240/681-1	-.290	-.0982	-.0768	-.0662	-.0411
680pF	1206 U2J 630V ±5%	8245/681-6	-.320	-.0864	-.0669	-.0576	-.0357
1.0nF	1206 NP0 100V ±5%	8240/102-1	-.290	-.0859	-.0666	-.0573	-.0355
1.0nF	1206 X7R 100V ±10%	8241/102-1	-.250	-.0699	-.0532	-.0457	-.0282
1.0nF	1206 X7R 630V ±10%	8241/102-6	-.260	-.0851	-.0658	-.0566	-.0351
1.0nF	1206 X7R 1 kV ±10%	8241/102-9	-.270	-.0907	-.0705	-.0607	-.0376
1.0nF	1206 X7R 2 kV ±10%	8241/102-8	-.350	-.1068	-.0839	-.0724	-.0449
1.5nF	1206 X7R 100V ±10%	8241/152-1	-.280	-.0717	-.0547	-.0469	-.0290
1.5nF	1206 X7R 630V ±10%	8241/152-6	-.290	-.0948	-.0740	-.0637	-.0395
2.2nF	1206 X7R 100V ±10%	8241/222-1	-.270	-.0675	-.0512	-.0439	-.0271
2.2nF	1206 X7R 630V ±10%	8241/222-6	-.280	-.0851	-.0658	-.0566	-.0351
2.2nF	1206 X7R 1 kV ±10%	8241/222-9	-.300	-.1005	-.0787	-.0678	-.0421
3.3nF	1206 X7R 100V ±10%	8241/332-1	-.280	-.0907	-.0705	-.0607	-.0376
3.3nF	1206 X7R 1 kV ±10%	8241/132-9	-.330	-.1005	-.0787	-.0678	-.0421
4.7nF	1206 X7R 100V ±10%	8241/472-1	-.270	-.0633	-.0477	-.0409	-.0252
4.7nF	1206 X7R 1 kV ±10%	8241/472-9	-.280	-.1005	-.0787	-.0678	-.0421
10nF	1206 X7R 100V ±10%	8241/103-1	-.250	-.0603	-.0452	-.0387	-.0239
10nF	1206 X7R 630V ±10%	8241/103-6	-.320	-.0948	-.0740	-.0637	-.0395
22nF	1206 X7R 100V ±10%	8241/223-1	-.280	-.0892	-.0692	-.0596	-.0370
22nF	1206 X7R 200V ±10%	8241/223-2	-.290	-.1083	-.0852	-.0735	-.0456
33nF	1206 X7R 630V ±10%	8241/333-6	-.300	-.1706	-.1371	-.1187	-.0739
47nF	1206 X7R 100V ±10%	8241/473-1	-.250	-.0660	-.0499	-.0428	-.0265
47nF	1206 X7R 250V ±10%	8241/473-2	-.300	-.1667	-.1339	-.1158	-.0721
100nF	1206 X7R 100V ±10%	8241/104-1	-.250	-.0583	-.0435	-.0372	-.0230
100nF	1206 X7R 250V ±10%	8241/104-2	-.270	-.0942	-.0734	-.0632	-.0392
1.0µF	1206 X7R 100V ±10%	8241/105-1	-.300	-.1078	-.0848	-.0731	-.0454
2.2µF	1206 X7R 100V ±10%	8241/225-1	-.680	-.2564	-.2086	-.1808	-.1127

weitere Werte auf Anfrage lieferbar

Baugröße 1210 Hochvolt max. Spannung 250 / 1000 V

Wert	Bauform/Keramik/Spg./Toleranz	Best.Nr.	ab 10	ab 100	ab 500	ab 1000	ab 2000
10nF	1210 X7R 1 kV ±10%	8251/103-9	-.450	-.2197	-.1784	-.1544	-.1101
22nF	1210 X7R 1 kV ±10%	8251/223-9	1.16	-.5029	-.4144	-.3596	-.2566
47nF	1210 X7R 630V ±10%	8251/473-6	-.910	-.3902	-.3205	-.2779	-.1983
100nF	1210 X7R 250V ±10%	8251/104-2	-.980	-.5585	-.4608	-.3999	-.2854
220nF	1210 X7R 100V ±10%	8251/224-1	-.450	-.1094	-.0865	-.0745	-.0530
220nF	1210 X7R 250V ±10%	8251/224-2	-.790	-.2614	-.2132	-.1846	-.1317
1.0µF	1210 X7R 100V ±10%	8251/105-1	-.390	-.1802	-.1455	-.1258	-.0896
2.2µF	1210 X7R 100V ±10%	8251/225-1	-.890	-.3206	-.2625	-.2275	-.1623

weitere Werte auf Anfrage lieferbar

Baugröße 1808 Hochvolt max. Spannung 1000 V / 2000 V / 3150 V

Wert	Bauform/Keramik/Spg. / Toleranz	Best.Nr.	ab 10	ab 100	ab 500	ab 1000	ab 4000
10pF	1808 NP0 3.15 kV ±10%	8290/100-7	-.97	-.3889	-.3194	-.2770	-.1976
12pF	1808 NP0 3.15 kV ±10%	8290/120-7	-.97	-.4556	-.3750	-.3253	-.2322
15pF	1808 NP0 3.15 kV ±10%	8290/150-7	-.97	-.3889	-.3194	-.2770	-.1976
22pF	1808 NP0 3.15 kV ±10%	8290/220-7	-.97	-.3889	-.3194	-.2770	-.1976
27pF	1808 NP0 3.15 kV ±10%	8290/270-7	-.97	-.3889	-.3194	-.2770	-.1976
33pF	1808 NP0 3.15 kV ±10%	8290/330-7	-.97	-.3889	-.3194	-.2770	-.1976
47pF	1808 NP0 3.15 kV ±10%	8290/470-7	-.97	-.3889	-.3194	-.2770	-.1976
1.0nF	1808 X7R 2 kV ±10%	8291/102-8	-.97	-.2983	-.2439	-.2113	-.1507
1.5nF	1808 X7R 2 kV ±10%	8291/152-8	-.97	-.2983	-.2439	-.2113	-.1507
2.2nF	1808 X7R 1 kV ±10%	8291/222-9	1.15	-.3889	-.3194	-.2770	-.1976

weitere Werte auf Anfrage lieferbar

Baugröße 1812 Hochvolt max. Spannung 250 / 630 / 1000 / 2000V

Wert	Bauform/Keramik/Spg. / Toleranz	Best.Nr.	ab 10	ab 100	ab 250	ab 500	ab 1000
1.0nF	1812 X7R 2 kV ±10%	8261/102-8	-.99	-.5555	-.4582	-.3977	-.2839
2.2nF	1812 X7R 2 kV ±10%	8261/222-8	-.99	-.5517	-.4551	-.3950	-.2819
4.7nF	1812 X7R 2 kV ±10%	8261/472-8	-.99	-.5555	-.4582	-.3977	-.2839
10nF	1812 X7R 1 kV ±10%	8261/103-9	-.75	-.2821	-.2304	-.1997	-.1424
10nF	1812 X7R 2 kV ±10%	8261/103-8	-.75	-.3003	-.2456	-.2128	-.1518
22nF	1812 X7R 630V ±10%	8261/223-6	1.05	-.3889	-.3194	-.2770	-.1976
33nF	1812 X7R 1 kV ±10%	8261/333-8	1.25	-.5828	-.4810	-.4175	-.2980
47nF	1812 X7R 1 kV ±10%	8261/473-8	1.45	-.7818	-.6469	-.5618	-.4010
100nF	1812 X7R 630V ±10%	8261/104-6	1.20	-.5185	-.4274	-.3709	-.2647
220nF	1812 X7R 250V ±10%	8261/224-2	1.10	-.5404	-.4457	-.3868	-.2761
330nF	1812 X7R 250V ±10%	8261/334-2	1.25	-.5282	-.4355	-.3779	-.2697
470nF	1812 X7R 250V ±10%	8261/474-2	1.35	-.6200	-.5120	-.4444	-.3172

weitere Werte auf Anfrage lieferbar

Nettopreise in € per St. ab Lager Nürnberg, zuzügl. der gesetzl. Mehrwertsteuer

MIRA-ELECTRONIC

Dipl. Ing. (FH) Gerhard Sauerbeck

www.MIRA-ELECTRONIC.de

info@MIRA-ELECTRONIC.de

Tel. 0911 / 55 59 19

Fax. 0911 / 58 13 41